



Since 1990 Northstone have specialised in the supply and installation of resin bonded and resin bound decorative surfacing. Our NorthDec surfacing systems require specialist skills in substrate preparation, mixing and application. Producing attractive textured, durable, low maintenance surfacing with appropriate slip resistance.

NorthDec has been used successfully on a wide range of projects including:

- Parks and gardens
- · Urban environmental improvement projects
- Heritage space
- · Coastal path
- New housing developments





NorthDec – Resin bonded Surfacing is a specialist hand applied surface treatment, consisting of thermosetting resin binder, dressed in a 'scatter coat' of kiln-dried aggregate. A wide range of aggregate is available comprising of different colours, shape and sizes. Typically laid at a thickness of approximately 3 mm when 1 – 3 mm aggregate is used.

NorthDec – Resin bound Surfacing is a specialist hand applied porous surfacing, consisting of thermosetting resin binder, mixed with kiln-dried aggregate. A wide range of aggregate is available comprising of different colours, shape and sizes. Typically laid at a thickness of 18mm using a blended mixture of 1–3 & 2-5mm aggregate.



Quality assurance is ensured by use of UKCA (or CE marked) materials and our ISO 9001 accreditation. NorthDec service life expectation is >20 years, depending on underlying substrate, traffic use and embraced maintenance regime. Slip resistance in wet and dry conditions is generally >40 USRV (≈ Pendulum Test Value) depending on aggregate choice.



**PEBBLE** 1-3, 3-6 & 6-10mm



WINTER QUARTZ 1-3, 2-5mm



**BLUE** 1-3, 2-5mm



QUARTZ 1-3, 2-5mm



NORDIC GREY 1-3, 2-5mm



QUARTZ

1-3, 2-5mm







## **TECHNICAL SUPPORT**

We offer tailored advice & solutions based on specific requirements for each Site.

For further information contact enquiries@northstone-ni.com See 'Downloads' on our website for the 'NorthDec' - Technical Data Sheets