

Material Application

ISOLINE® APRON FLASHING is a corrugated apron flashing piece, designed to seal the gap between ISOLINE corrugated sheets, and a vertical wall abutment for complete waterproofing and a seamless finish.

Application

- Ensures complete waterproofing at the wall abutment
- The ISOLINE® APRON FLASHING corrugated profile perfectly matches the Onduline ISOLINE LOW LINE underroofing sheets for guaranteed waterproofing.

Features & Benefits

- Complete waterproofing at the wall abutment
- Made from polypropylene (PPE) to withstand excess heat
- Installation is quick and easy.

Technical characteristics

DIMENSIONS & WEIGHT

Material	Polypropylene
Length (mm)	870
Width (mm)	190
Height (mm)	80
Weight (kg)	0.35
Thickness (mm)	1.2

PACKAGING

Pallet Qty	500
Pallet Weight (kg)	206
Carton Qty	25
Carton Weight (kg)	9
Carton Dimensions (mm)	290 x 125 x 960



Color



Black

Warranty

All the claims will be considered with respect to application recommendations issued by Onduline company.

Installation

The product should be installed in accordance with the manufacturers' installation guidelines. For more details, please seek professional advice or contact enquiries@onduline.net.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

onduline.co.uk

The Whitechapel Building
10 Whitechapel High Street
Aldgate | London
E1 8QC